

2-100.02 Swinghandle RS 130

for cutout 130, for round rods, for profile-cylinder



Low Profile Swinghandle for sheet metal and plastic enclosures.

- RH or LH application.
- The polyamide handle is fully insulated.
- The handle is locked by a profile-cylinder according to DIN 18252 or a KABA Ø22 (0.866) round cylinder.
- Water- and dust-tight according to IP65 DIN EN 60529.

Material:

- a), b) and c)
- **Swinghandle:** zinc die, black or PA, black
- d) and d1)
- **3- and 2-point cam:** steel, zinc plated
- e)
- **Round rods:** steel, zinc plated
- f)
- **Adapter:** zinc die, untreated
- g) and k)
- **Rod Guide and adapter:** PA, black



	Cutout 130/Ø46	Cutout 130/□46	see page
a) Swinghandle, PA (black) for profile-cylinder 40mm long	207-9001	207-9311	
a1) as a), but with cylinder dustcover	207-9002	207-9312	
a2) Swinghandle, zinc die (black) for profile-cylinder 40mm long	207-9008	-	
a3) as a2), but with cylinder dustcover	207-9009	-	
a4) as a1), but 5mm raised for profile-cylinder 45mm long with cover	207-9003	207-9313	
a5) as a4), but Swinghandle, zinc die (black), door dish, PA black for profile-cylinder 45mm long	207-9004	207-9314	
b) Swinghandle for Ø 22 KABA cylinder on request			
c) Swinghandle, PA (black) with padlock device (AISI 304) for profile-cylinder	207-9006	on request	
Optional:			
d) 3-point-cam e.g. for bending	A20 207-9522	207-9522	03.45
	A26 207-9528	207-9528	
d1) 2-point-cam	207-9599	207-9599	
e) Round rods			02.97, 02.98
f) Adapter for round rods			02.103, 02.102
g) Rod guide for bending A20	200-3601.03	200-3601.03	02.99, 02.101
Rod guide for bending A26	200-3602.03	200-3602.03	
h) Profile-cylinder according DIN 18252			03.42, 03.43
i) KABA cylinder Ø 22 round cylinder on request			
k) Adapter to allow installation into 2 holes Ø46 and □46. In this case the same door can be used RH or LH.	207-2701.03	207-2702.03	
k1) Gasket for adapter	207-2804	207-2803	

2-100.02 Swinghandle RS 130

for cutout 130, for round rods, for profile-cylinder

