

# EFR-1 Single Module Earth Leakage Relay

## SPECIFICATION

Control Voltage	: 110 or 240v
Trip Current	: 20mA - 500mA (factory set)
Time Delay	: Instantaneous, 60mS or 300mS (factory Set)
Frequency Range	: 30/120Hz
Temperature Range	: -20 degree C to +55 degree C
Relative Humidity	: 95% non condensating
Output Relay	: SP volt-free changeover contacts Rated 250V 125VA
Core Balance C.T.	: External (see separate data sheet)
Controls	: Integral Test button
Connections	: Screw clamp terminals

Dimensions : 90mm x 17.5mm x 60mm (H x W x D)

DESCRIPTION	ORDER REFERENCE
Integral Test Button	EP EFR1**
Remote Test Button	EP EFR1RTB**
** State Voltage, Trip current, Time delay required when ordering.	

In line with our policy of constant improvements, we reserve the right to vary the specifications contained in this leaflet.

The services of our Technical support staff are available for assistance or guidance on earth leakage problems and possible solutions please contact us at:

FDB Electrical Ltd

Tel: 020 8568 4621  
Fax: 020 8569 7899  
Email: [rcdsales@fdb.uk.com](mailto:rcdsales@fdb.uk.com)



A member of the Group owned by  
**Findlay Durham & Brodie Ltd**  
Partnership (Est 1852)

We manufacture a complete range of electrical safety products. Please contact us for further details.