

EFR-4/EFR-5 Universal Earth Leakage Protection Relay

SPECIFICATION

Control Voltage	: 24-240V AC/DC non isolated 240/415V 30-120Hz internally isolated
Trip Current	: 10mA to 2Amps (factory set)
Time Delay	: 20mSecs to 1 Second (factory set)
Frequency Range	: 5Hz - 800Hz (Monitoring)
Temperature Range	: -10 degree C to +55 degree C
Relative Humidity	: 95% non-condensating
Output Relay	: Separate N/C and N/O contacts Rated 8 Amps 2000VA 415V max
Core Balance C.T.	: EFR-4 Integral - 28mm I.D. EFR-5 Integral - 46mm I.D.
Controls	: Integral test, reset push button Power On - Green LED Earth Fault Trip - Red LED
Connections	: Colour coded flying leads (500mm) :

Dimensions : 70mm x 100mm x 100mm (H x W x D)

CONTROL VOLTAGE	ORDER REFERENCE	
	EFR-4	EFR-5
24-250V AC/DC	EP EFR41**	EFR51**
240-415V 30-120Hz	EP EFR42**	EFR-52**
** State Voltage, Trip current, Time delay required when ordering.		

In line with our policy of constant improvements, we reserve the right to vary the specifications contained in this leaflet.

The services of our Technical support staff are available for assistance or guidance on earth leakage problems and possible solutions please contact us at:

FDB Electrical Ltd

Tel: 020 8568 4621
Fax: 020 8569 7899
Email: rcdsales@fdb.uk.com



A member of the Group owned by
Findlay Durham & Brodie Ltd
Partnership (Est 1852)

We manufacture a complete range of electrical safety products. Please contact us for further details.