

# EFU50 DC Earth Fault Monitor

## SPECIFICATION

Control Voltage : 110V dc nominal (Ac on request) +25 -30% (V nom)

Trip Range : 500mA to 2000mA (factory set)

Monitoring Range : 12V to 1000V dc

Temperature Range : -25 degrees C to +55 degrees C

Relative Humidity : 95% non condensating

Output Relay : Separate N/O & N/C contacts  
Rated 8 Amps 2000VA (415V max)

Core Balance C.T. : Integral 28mm or 46mm (please specify)

Controls : Integral Test, reset push button  
Power On - Green LED  
Earth Fault Trip - Red LED

Connections : Terminal connections

Dimensions : 70 X 150 X 100mm (HXWXD)

CORE BALANCE C.T.	ORDER REFERENCE
28mm I.D	EP EFU50/28**
46mm I.D	EP EFU50/46**
** State control voltage, trip current required when ordering.	

In line with our policy of constant improvements, we reserve the right to vary the specifications contained in this leaflet.

The services of our Technical support staff are available for assistance or guidance on earth leakage problems and possible solutions please contact us at:

**FDB Electrical Ltd**

Tel: 020 8568 4621  
Fax: 020 8569 7899  
Email: [rcdsales@fdb.uk.com](mailto:rcdsales@fdb.uk.com)



A member of the Group owned by  
**Findlay Durham & Brodie Ltd**  
Partnership (Est 1852)

We manufacture a complete range of electrical safety products. Please contact us for further details.