

VEF2 Variable Earth Leakage Protection Relay

SPECIFICATION

Control Voltage	: 24-240V AC/DC
Trip Current	: 0.02Amps to 30Amps over three built in ranges
Time Delay	: 20mSecs to 2 Seconds over two built in ranges
Frequency Range	: 5Hz - 800Hz (Monitoring)
Temperature Range	: -15 degree C to +55 degree C
Relative Humidity	: 95% non-condensating
Output Relay	: Volt-free changeover contacts rated 5Amp 1250VA
Core Balance C.T.	: Full range of external C.T's round, rectangular and split core versions.
Controls	: Integral test, reset push button
Indications	: Power On - Green LED Earth Fault Trip - Red LED
Connections	: Terminal Connections

Dimensions : 70mm x 75mm x 95mm (H x W x D)

CONTROL VOLTAGE	ORDER REFERENCE
24-250V AC/DC	EP VEF2I

In line with our policy of constant improvements, we reserve the right to vary the specifications contained in this leaflet.

The services of our Technical support staff are available for assistance or guidance on earth leakage problems and possible solutions please contact us at:

FDB Electrical Ltd

Tel: 020 8568 4621
Fax: 020 8569 7899
Email: rcdsales@fdb.uk.com



A member of the Group owned by
Findlay Durham & Brodie Ltd
Partnership (Est 1852)

We manufacture a complete range of electrical safety products. Please contact us for further details.