

VEF4/VEF5 Variable Earth Leakage Protection Relay

SPECIFICATION

Control Voltage	: 24-240V AC/DC
Trip Current	: 20mA to 2Amps over two built in ranges
Time Delay	: 20mSecs to 2 Seconds over two built in ranges
Frequency Range	: 5Hz - 800Hz (Monitoring)
Temperature Range	: -10 degree C to +55 degree C
Relative Humidity	: 95% non-condensating
Output Relay	: Volt-free changeover contacts rated 5Amp 1250VA
Core Balance C.T.	: EFR-4 Integral - 28mm I.D. EFR-5 Integral - 46mm I.D.
Controls	: Integral test, reset push button
Indications	: Power On - Green LED Earth Fault Trip - Red LED
Connections	: Terminal Connections (Flying leads on request)
Construction	: Totally encapsulated and housed in flame retardant ABS enclosure Din-rail or chassis mounting
Dimensions	: VEF4 70mm x 75mm x 95mm (H x W x D) VEF5 70mm x 100mm x 100mm (H x W x D)

CONTROL VOLTAGE	ORDER REFERENCE	
	VEF4	VEF5
24-250V AC/DC	EP VEF4I	EP VEF5I

In line with our policy of constant improvements, we reserve the right to vary the specifications contained in this leaflet.

The services of our Technical support staff are available for assistance or guidance on earth leakage problems and possible solutions please contact us at:

FDB Electrical Ltd
 FDB Electrical Ltd, Woodall Road
 Hemmford, Middlesbrough TS10 7HE

Tel: 020 8568 4621
 Fax 020 8569 7899



A member of the Group owned by
Findlay Durham & Brodie Ltd
 Partnership (Est. 1852)

We manufacture a complete range of electrical safety products. Please contact us for further details.