

# 7-087 Flush-mounted Compression Latch L28/L37 with knurled wheel adjustment Stainless Steel



DIN  
61373



15  
Nm

RoHS  
WEEE

## Advantages

- Compression 6 mm.
- Flush-mounted version.
- Vibration-proof according to DIN EN 61373.
- RH and LH version.
- Indication of opened/closed position on the housing edge and the insert.
- The H-dimension can be varied via the cranking of the cam.
- The cam can be varied to  $\pm 11$  mm (GL28) and  $\pm 6$  mm (GL37) via provided catch with knurled wheel on the axis.

## Materials

- **Housing, insert, axis, nut:** stainless steel AISI 316L
- **Anti-rotation device:** stainless steel AISI 316
- **Catch:** PA, black
- **Stop washer:** stainless steel

## Remarks

Door thickness (s) max. 13mm at GL 28mm  
Door thickness (s) max. 22mm at GL 37mm  
Door thickness (s) min. 1.8mm  
Negatively bent cams cannot be installed pre-assembled.

1. Compression 6mm
2. Nut
3. Anti-rotation device (included in scope of delivery)
4. Washer when using cylinder head screws or weld studs/nuts
5. Catch with knurled wheel adjustment



## Flush-mounted Compression Latch with insert, RH version, closing left

|    | Part Number       | Insert             | Compression | Housing length | Door thickness (S) | Installation type |
|----|-------------------|--------------------|-------------|----------------|--------------------|-------------------|
| a) | 148-9502.00-00000 | Square 8mm         | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| a) | 148-9503.00-00000 | Double bit 3mm pin | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| a) | 148-9507.00-00000 | Triangular 8mm     | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| a) | 148-9508.00-00000 | Conical square 9mm | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| b) | 148-9602.00-00000 | Square 8mm         | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |
| b) | 148-9603.00-00000 | Double bit 3mm pin | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |
| b) | 148-9607.00-00000 | Triangular 8mm     | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |
| b) | 148-9608.00-00000 | Conical square 9mm | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |

## Flächenbündiger Kompression-Drehriegel mit Betätigung, linke Version, rechts schließend

|    | Part Number       | Insert             | Compression | Housing length | Door thickness (S) | Installation type |
|----|-------------------|--------------------|-------------|----------------|--------------------|-------------------|
| a) | 148-9552.00-00000 | Square 8mm         | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| a) | 148-9553.00-00000 | Double bit 3mm pin | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| a) | 148-9557.00-00000 | Triangular 8mm     | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| a) | 148-9558.00-00000 | Conical square 9mm | 6 mm        | 28 mm          | max. 13 mm         | screw-on          |
| b) | 148-9652.00-00000 | Square 8mm         | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |
| b) | 148-9653.00-00000 | Double bit 3mm pin | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |
| b) | 148-9657.00-00000 | Triangular 8mm     | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |
| b) | 148-9658.00-00000 | Conical square 9mm | 6 mm        | 37 mm          | max. 22 mm         | screw-on          |

### \* Accessories

6-100 **Key**

7-105.01 **Cams L35/45 Stainless Steel**

7-077 **Height Adjustable Cam L45 Stainless Steel**

### \* Specific accessories

