

1-110.01 Quarter-Turn Pr20.1 L36



Advantages

- Flat quarter-turn for cutout Pr20.1.
- RH / LH application.
- IP65/67 according to DIN EN 60529 by sealing kit. (optional).
- Please configure the quarter-turn with insert (adapter) and cam.
- On request parts can be assembled.
- The quarter-turn can be screwed into the cutout with the pre-assembled cam.

Materials

- **Housing:** zinc die, matte chrome plated, glossy chrome plated or black
- **Nut:** steel, zinc plated
- **Grounding nut:** zinc die, untreated

Remarks

Door-thickness (S) max. 26mm



Quarter-Turn housing

	Part Number	Surface	Grounding type	IP protection	Installation type
a)	100-9065.40-00036	matte chrome plated			screw-on
a)	100-9065.31-00036	glossy chrome plated			screw-on
a)	100-9065.00-00000	black			screw-on
a)	100-9070.00-00036	matte chrome plated	Grounding nut	IP65/67	screw-on
a)	100-9068.00-00036	glossy chrome plated	Grounding nut	IP65/67	screw-on
a)	100-9066.00-00036	black	Grounding nut	IP65/67	screw-on

+ **Optional accessories**

- c) 100-9206.00-00024 Adapter set L36

+ **Function extension**

- e) 209-9006.00-00000 Sealing kit IP65/IP67 for Quarter-Turns Pr20.1 L30-60

***** **Accessories**

- d) 1-102 Cams L35/45 Steel
- d) 1-260 Hooked Cam
- d) 1-261 Cams with Ramp
- d) 1-262 Cams variable
- 1-101 Inserts Pr20.1

