

1-410 2-Point Rod Latch RS



Advantages

- For cutout Pr 20.1.
- For rods with thread M8/M10.
- Closing rotation 180°.
- RH and LH version.
- In combination with lock support for bending 20 or 26mm.
- Escutcheon with insert PS 1-430.01.
- T- und L-handles PS 1-430.
- Swinghandles RS 130 see PS 2-300.

Materials

- **Housing:** steel, zinc plated
- **Gear and connectors:** zinc die, chrome plated

Remarks

- (S) Door-thickness 1.5 - 2.5mm
1. Stroke 31.4mm
 2. For painted doors and bolted lock, an M6 x 8 weld stud with nut is required for the earthing



Rod Latch

	Part Number	Rod diameter Ø	Version	Installation type
a)	235-9009.00-00000	8 mm	RH version	screw-on
a)	235-9010.00-00000	8 mm	LH version	screw-on
a)	235-9011.00-00000	10 mm	RH version	screw-on
a)	235-9012.00-00000	10 mm	LH version	screw-on



Specific accessories

201-0801.00-01000 **Round rod, M8 x 1000mm**

201-1001.00-01000 **Round rod, M10 x 1000mm**

* Accessories

- e) 1-430 T- and L-Handles for Rod Latches
- e) 2-300 Swinghandle RS 130 for Rod Latch
- d) 1-192 Rod Guides RS
- d) 1-193 Rod Guide RS
- d) 1-190 Rod Guides RS
- d) 1-191 Height-adjustable Rod Guide RS
- b1) 235-1002.00-00000 Lock support A26
- b) 235-1001.00-00000 Lock support A20
- e) 1-430.01 Escutcheon and Inserts
 - 203-0606.03-00000 Bushing Ø10
 - 203-0605.03-00000 Bushing Ø8

