

# 7-081.02HD Hygiene Quarter-Turn with T-Handle Pr20.1 L18



Specially developed Hygiene stainless steel Quarter-Turn with T-handle (HD, Hygienic design), for applications in the food sector and hygienic areas

## Advantages

- Tested according to: GS-NV 2:2013/06 Principles for the testing of food processing machines GS-NV 6:2013/06 Principles for the testing of hygiene requirements. Machine Ordinance: DIN EN 1672-2:2009
- DGUV Test Certificate.
- Dirt resistant and easy to clean by means of polished surface and transition radii.
- RH / LH application.
- IP 65/67/69K according to DIN EN 60529 / DIN 40050.
- Cam can be delivered pre-assembled upon request.
- A pre-assembled Quarter-Turn can be installed in the cutout.
- Grounding by grounding nut.

## Materials

- **Housing, handle and grounding nut:** AISI 316
- **Serrated screw:** AISI 304
- **Seal:** silicone, blue, FDA conform (Food and Drug Administration)

## Remarks

- (S) Door-thickness max. 8mm  
1. Silicone seal



## Hygiene Quarter-Turn with T-Handle

	Part Number	Housing length	Installation type
a)	100-9313.00-00000	18 mm	screw-on

b) 7-105 Cams L35/45 Stainless Steel

