

7-060 Swinghandle FS PrC Stainless Steel for PHZ



Advantages

- Swinghandle for profile cylinder to DIN 18252.
- IP65 DIN EN 60529 within the sealed area.
- The padlock device with rectangular base is fitted from the rear and so held captive between door and swinghandle body.
- This opening can be filled with a rectangular blanking plate.

Materials

- **Swinghandle, dish, bearing part, dust cover and padlock bolt:** AISI 316
- **Blanking plate:** AISI 304
- **Swinghandle shaft:** AISI 303
- **Cap:** PA, black

Remarks

(S) Door-thickness 1.5 - 2.5mm
Swinghandle for application with rod latch see product system 7-040 and cutout version PrC 50x25mm.



Swinghandle for profile cylinder

	Part Number	Cylinder cover	Padlock	Installation type	Delivery Unit
a)	207-9292.00-00000			screw-on	1 pc.
a)	207-9293.00-00000	Yes		screw-on	1 pc.
a1)	107-9286.00-00000	Yes	Yes	screw-on	1 pc.
a1)	107-9287.00-00000		Yes	screw-on	1 pc.

- b) 207-2506.80-00000 Blanking plate for opening
- c) 2-140 Profile-Cylinder DIN 18252
- c) 7-069 Profile-Cylinder Stainless Steel
- d) 7-040 Rod Latch FS PrC Stainless Steel

