

# 1-155.02 Quarter-Turn with T- Handle and Wing Knob Pr20.1 L30-60



## Advantages

- Quarter-turns with extended housing.
- Maximum door-thickness 50mm.
- All versions of wing-handles are supplied complete with housing.
- Versions **without cylinder** IP65 according to DIN EN 60529.
- Versions **with cylinder** IP54 according to DIN EN 60529.
- Grounding by single sided grounding nut (1.).
- All lockable handles supplied with 2 keys.

## Materials

- **T-handle:** PA, black with zinc die core, or zinc die, chrome plated or black
- **Housing:** zinc die, black
- **Flat external seal:** NBR/Perbunan, black
- **Wing knob:** PA, black with zinc die core
- **Grounding nut:** zinc die

## Remarks

(S) Door-thickness see table  
 Housings with L 36mm on request.  
 Detailed dimensions of the handles see product system 1-130, 1-140.  
 Part No. for PAGODA version with master key system on request.  
 Please configure the quarter-turn with a cam.  
 1. grounding nut



## Quarter-Turn with wing knob, PA, black

	Part Number	Housing length	Latching type	Door-thickness (S)	IP protection	Installation type	Delivery Unit
b)	200-9323.00-00000	40 mm		max. 30 mm	IP65	screw-on	1 pc.

- c) 1-102 Cams L35/45 Steel
- c) 1-262 Cams variable

